

## ANS04E IP65 Ambient Noise Sensor (Extended Temperature Range)

The ANS04E is an IP65 rated Ambient Noise Sensor designed to operate under extreme temperatures, from -40°C to +50°C. The ANS work with the whole range of ASL Public Address and Voice Alarm systems and VIPA IP-based systems.

The purpose of an Ambient Noise Sensor (ANS) system is to adjust the level of public address announcements based on a measure of the ambient noise in the PA zone. This will maintain a set volume of public address audio above the ambient noise, in order to guarantee that the announcement is intelligible, yet at a comfortable level.



Each Public Address or Voice Alarm system is able to support the connection of multiple ANS04E units, each of which interfaces to an analogue input of a BMB01 Remote I/O Unit. The ANS sensor detects ambient noise using its built-in microphone. The detected signal is weighted with a speechband response for the best system performance, and is then translated to a value of measured ambient noise in dBA. This value is used to proportionally adjust the Public Address or Voice Alarm system output gain for the configured output channel or channels.

The system is set up for the maximum broadcast volume without the ANS sensor, and the ANS system then reduces the gain from this level when the zone is quiet.

Two ambient noise measurement ranges are selectable, depending on the required system volume and expected ambient noise level:

- High Range from 65 dBA to 95 dBA
- Low Range from 55 dBA to 85 dBA

The ANS range is selectable via internal switch, and is identified by external LEDs. These LEDs also provides a useful visual indication of the unit's operation, as their brightness varies with the ambient noise level. There are also two internal status LEDs, for use in installation and fault finding. A green LED indicates the presence of power when lit, and an amber LED illuminates in the event of a microphone capsule open or short circuit fault.

The ANS04E is housed in an IP65 rated die-cast aluminium enclosure, with the electronics and microphone being mounted on the front plate. A wall mount bracket with swivel is provided for precise positioning of the ANS sensor. A cover is also provided in order to protect the built-in microphone from adverse weather conditions including rain, sleet, and snow. The connection between the ANS04E and a BMB01 Remote I/O Unit is simple 3-wire link.

For further details, and for information on other products, please visit [www.asl-control.co.uk](http://www.asl-control.co.uk).

## SPECIFICATION

### General

Supply Voltage Range..... 21 – 40 V DC  
Current Consumption ..... 35 mA @ 24 V DC supply  
Output Current..... 4 – 20 mA nominal  
Ambient Noise Measurement Range<sup>1</sup>...65 – 95dBA (High Range)  
55 – 85 dBA (Low Range)<sup>2</sup>

### Number of ANS Sensors

Routers..... max. 12 per PA zone  
(sensors for one zone must be  
connected to the same BMB01 Remote I/O Unit)

VIPA Systems ..... any number of ANS sensors  
configured on the unit

Enclosure..... die-cast aluminium  
Grey NCS S1002-B 20% GLOSS LSOH

Weather Cover ..... steel  
Grey NCS S1002-B 20% GLOSS LSOH

Bracket .....aluminium / silver

### Environmental

Temperature (storage and operating) ..... –40°C to +50°C  
(±3 dB accuracy)

Humidity Range .....0% to 93% non-condensing

Ingress Protection ..... IP65

### Dimensions and Weight

#### Enclosure

Dimensions (H x W x D) ..... 160 mm x 100 mm x 81 mm

Gland / Conduit Hole ..... 20.2 mm

Weight ..... 1020 g (with internal components)

#### Weather Cover

Dimensions (H x W x D) ..... 101.4 mm x 162.8 mm x 163 mm

Weight .....500 g

#### Bracket

Dimensions (H x W x D) ..... 113 mm x 64 mm x 165 mm  
(approx.)

Cable Pass-Through Hole ..... 14 mm

Weight .....150 g



<sup>1</sup> Ambient Noise Measurement Range is selectable via internal switch.

<sup>2</sup> Low range ANS is not supported by all Router software versions. Please refer to ASL.



This equipment is designed and manufactured to conform to the following EC standards:

EMC: EN55103-1/E1:1997, EN55103-2/E5:1997, EN50121-4:2006, ENV50204:1996

Safety: EN 60065:2002

#### Manufacturer

Application Solutions (Safety and Security) Limited

Unit 17 - Cliffe Industrial Estate - Lewes - East Sussex - BN8 6JL - U.K.

Tel: +44(0)1273 405411 Fax: +44(0)1273 405415

www.asl-control.co.uk



All rights reserved.

Information contained in this document is believed to be accurate, however no representation or warranty is given and Application Solutions (Safety and Security) Limited assumes no liability with respect to the accuracy of such information.