



The M200 is one of a range of high efficiency Class D Amplifiers for Public Address and Voice Evacuation applications. The amplifier is part of a modular system, and is housed in a V400 Amplifier Mainframe. The Amplifier Mainframe can carry various amplifier types, and carries interface cards which contain the amplifier's monitoring electronics. The M200 will deliver 200 W to a 100 V loudspeaker line, even with the Amplifier Mainframe's 230 V mains supply absent and right down to a 21 V battery supply voltage.

The unique design negates the need to 'sleep' the amplifiers when in quiescent state. This improves efficiency and reduces heat dissipation.

For further details, and for information on other products, please visit [www.asl-control.co.uk](http://www.asl-control.co.uk).

## SPECIFICATION

---

### General

Output Power .....	200 W (@ 100 V RMS down to 21 V battery supply) See Note <sup>1</sup> regarding performance when on 230 V mains supply
Output Voltage and Input sensitivity .....	100 V RMS into 50 $\Omega$ load for 0 dBu 1 kHz input signal
Regulation .....	No load to full load, better than 1.5 dB
Efficiency .....	80%
Frequency Response .....	100 Hz – 18 kHz ( $\pm 3$ dB)
Total Harmonic Distortion (@ 100V RMS output, full load) .....	<0.5%
Residual Noise .....	Better than 80 dB (A-weighted) below full output
Quiescent Current (no signal, @ 24V supply) .....	70 mA
Quiescent Current (surveillance signal, @ 24V supply) .....	140 mA, nominal
Quiescent Current in sleep state .....	60 mA
Full Power Current (worst case 21V battery supply) .....	12.5 A
Fusing .....	1 x F15A 1 $\frac{1}{4}$ "

---

### Dimensions and Weight

Dimensions (H x W x D) .....	79 mm x 158 mm x 290 mm
Weight .....	2.7 kg

---

### Environmental

Temperature (Storage and Operating) .....	-5 °C to +50 °C
Humidity Range .....	0% to 93% Non-condensing

<sup>1</sup> ASL amplifiers are specified to deliver their rated power at the lowest battery voltage (21 V). However, on mains power they can produce full output, with normal programme material, into loads 25% greater than those specified. The M200 will deliver full output with 250 W of load connected.



This equipment is designed and manufactured to conform to the following EC standards:

EMC EN 55103-1 Environment E1, EN 55103-2 Environment E5

Safety EN60065

Manufacturer  
Application Solutions Limited  
Safety, Security and Control Division  
Unit 17 - Cliffe Industrial Estate - Lewes - East Sussex - BN8 6JL - U.K.  
Tel: +44(0)1273 405411 Fax: +44(0)1273 405415  
www.asl-electronics.co.uk



All rights reserved.

Information contained in this document is believed to be accurate, however no representation or warranty is given and Application Solutions Limited assumes no liability with respect to the accuracy of such information.